

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
1	1	PLASMA CUTTER, THERMAL DYNAMICS PAK MASTER 100 XL PLUS , new 2001, S/N 01150908
2	1	AIR COMPRESSOR, SPEEDAIRE , 3 HP motor, 230/460 v.
3	1	ELECTRIC CHAIN HOIST, COFFING 1 T. CAP.
4	1	ELECTRIC CHAIN HOIST, BUDGIT T. CAP.
5	1	ELECTRIC CHAIN HOIST, BUDGIT 1/2 T. CAP.
6	1	ELECTRIC CHAIN HOIST, COFFING 1 T. CAP.
7	1	ELECTRIC CHAIN HOIST, BUDGIT T. CAP.
8	1	DRILL PRESS, CAL-HAWK , 5-spd.
8A	1	LOT OF BUTTERFLY VALVES , 10" (approx. 3)
9	1	LOT OF PNEUMATIC IMPACT GUNS, INGERSOLL-RAND
10	1	LOT OF PNEUMATIC IMPACT GUNS, INGERSOLL-RAND & AIRETOOL
11	1	LOT OF PNEUMATIC IMPACT GUNS, AIRETOOL
12	1	LOT OF PNEUMATIC IMPACT GUNS, AIRETOOL
13	1	LOT OF PNEUMATIC TOOLS, AIRETOOL
14	1	LOT OF PNEUMATIC RIVET GUNS
15	1	LOT OF PNEUMATIC TOOLS
16	1	LOT OF PNEUMATIC HAMMERS, INGERSOLL-RAND
17	1	SHOP FAN, CUSTOM 60"
18	1	ROLL-AROUND TOOLCHEST, WATERLOO
19	1	PIPE STAND, RIDGID MDL. 460
20	1	PIPE BENDER, NORTHERN , w/dies
21	1	DOUBLE END GRINDER, H.D.
22	1	DOUBLE END GRINDER, H.D.
23	1	DOUBLE END GRINDER
24	1	SANDBLASTER, CRAFTSMAN
25	1	LOT CONSISTING OF 3-WHEEL TORCH CART & 4' X 4' ROLLING PLATFORMS (2)
26	1	WELDING MACHINE, MILLER SYNCROWAVE 350 , 350 amps @ 34 v. (40% duty cycle), 300 amps @ 32 v. (60% duty cycle), 1 ph., 3-400 amps welding amperage range, AC/DC TIG (GTAW), pulsed TIG (GTAW-P), stick (SMAW), min. 0.012"/max. 0.625" (steel), min. 0.015"/max. 0.500" (aluminum), S/N KA977384
27	1	TOOL TYPE PORTABLE EDM MACHINE, CHEVALIER (HSIU FONG MACHINERY CO.) MDL. ALIC-1 (TAP DISINTEGRATOR) , 2-5/16" quill stroke, 22 lbs. load cap., 15 amps, 24 gal. dielectric fluid cap., fluid return plate, 3-axis slide assembly, adj. electrode holder, S/N 081001
28	1	ARC WELDER, LINCOLN IDEALARC MDL. DC600 , 600 amps, w/LN-7 wire feeder, S/N AC730450
29	1	LOT OF WELDING MACHINES: MILLERMATIC MDL. 150, MILLERMATIC MDL. 200, LINCOLN IDEALARC MDL. 250
30		VERTICAL TURRET MILL, LAGUN MDL. FTV4 , new 1985, 11" x 58" table, pwr. feed in all directions, variable spdl. spds: 70-4200 RPM, Anilam 2-axis D.R.O., coolant pan, 1-shot lubrication, S/N 22063
31	1	VERTICAL TURRET MILL, ACER ULTIMA MDL. 4VK , 10" x 50" table, harden & ground ways, variable spdl. spds: 70-3600 RPM, long. pwr. feed, 2 HP drive, 30" X-axis travel, 12" Y-axis travel, 16" Z-axis travel, 5" quill travel, 1-shot lubrication, Fagor 2-axis D.R.O., S/N 9412843A

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
32	1	NIBBLER, PULLMAX TYPE P-9 , 4" throat, cuts up to 3/8" material, S/N 58380-09
33	1	NIBBLER, PULLMAX TYPE P-9 , 4" throat, cuts up to 3/8" material, S/N 510040-2
34	1	PRESS, SWAINE 45 T. CAP. , Mdl. 35A
35	1	PRESSBRAKE, VERNON , approx. 15 T. cap.
35A	1	NOTCHER, KIDDER MFG. MDL. 4313 , S/N IE7-32
36	1	IRONWORKER, DVORAK MDL. UNI-HYDRO 42-14 , 42 T. cap., S/N 3P4496
37	1	PRESS, KIDDER 25 T. CAP. , Mdl. DP-24X, 24" throat, S/N NK-357
38	1	WOODCUTTING BANDSAW, JET MDL. WBS-28-3 , 5 HP motor, 220/440 v., 3 ph, S/N 970023
39	1	VERTICAL BANDSAW, ROCKWELL MDL. 20 , S/N 1799822
40	1	VERTICAL WOODWORKING BANDSAW, NORTHFIELD 36" , approx. 3,000 lb. cap., 5 HP motor, 460v/3 ph/60 Hz
41	1	VERTICAL BANDSAW, HOBART FOOD GRADE
42	1	ABRASIVE CHOP SAW, TOLEDO-BEAVER TOOL , 20" blade
43	1	PIPE BENDER
44	1	PIPE BENDER
45	1	ROTARY SCREW TYPE AIR COMPRESSOR, INGERSOLL RAND MDL. SSR2000 , 75 HP motor
46	1	HORIZONTAL AIR COMPRESSOR , 100 gal. tank, 15 HP motor
47	1	VERTICAL AIR COMPRESSOR, CAMPBELL-HAUSFELD , 100 gal. tank, 5 HP motor
47A	1	AIR COMPRESSOR, U.S. MDL. US15 , 15 HP motor, 100-115 PSI, S/N 105370
48	1	LOT OF AIR RECEIVING TANKS (2)
49	1	AIR DRYER, DELTECH PYRAMID MDL. 2000
50	1	VERTICAL MILL, BRIDGEPORT SERIES 19" X 42" , R-8 spdl. taper, 5" spdl. travel, spdl. spds: 60–4200 RPM, 9" x 42" table, (3) T-slots, 300 lb. load cap., 30" table long. travel, 12" cross travel, 16" knee vert. travel, +/- 45 deg. F-B head swivel, +/- 90 deg. head swivel L-R, 2 HP motor, Newall 2-axis D.R.O. expandable to 3 axis, S/N 204861
51	1	VERTICAL KNEE MILL, MAXMILL , 42" x 9" table, 3 T-slots, 0.625" on 2.5" centers, R8 spdl., (8) spdl. spds: 80–2720 RPM, 1.875" dia. spdl., 3.375" quill dia., 5' spdl. travel, 12" table cross travel, 23" table long. travel, 16" vert. travel, +/- 45 head tilt forward – back, 90 head tilt left - right, 2 HP motor, S/N 7607560
52	1	PLAIN HORIZONTAL MILL, BROWN & SHARPE NO. 2 MANUAL TYPE , 7-1/2" x 40-1/4" table working surface, 10" x 50-1/2" table overall, (3) 5/8"W. T-slots, (18) spdl. spds: 40–1530 RPM, 3 HP motor, horiz. spdl., vert. spdl., S/N 6251
52A	1	STARTER, SAFTRONICS MDL. 2033641 , 50-60 HZ in/out, 420 amps in/0-420 out, 350 HP in
52B	1	STARTER, SAFTRONICS MDL. 2033641 , 50-60 HZ in/out, 420 amps in/0-420 out, 350 HP in
53	1	ENGINE LATHE, SUMMIT 30" X 160" , new 1989, 33" sw. over bed, approx. 25" sw. over crossslide, 4.15" spdl. hole, spds: 14-1010 RPM, inch/metric thdng., taper attach., pwr. rapid traverse, 12" dia. 3-jaw chuck

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
54	1	ENGINE LATHE, LODGE & SHIPLEY 24" X 120" , Mdl. 20, 14" over crossslide, spds: 9-500 RPM, fds: 0.0025-0.160 IPR, thds:1-64 TPI, 4" tailstock quill dia., 12" tailstock quill travel, 21-1/4"W. bed, chuck guard, taper attach., steadyrest, S/N 35570
55	1	ENGINE LATHE, LODGE & SHIPLEY 20" X 120" , 11" sw. over crossslide, (24) spdl. spds: 9- 500 RPM, 2-3/4" spdl. hole, Morse No. 6 spdl. taper, (60) fds: 0.0025-0.160 IPR, (60) thds: 1-64 TPI, 1-3/4" tailstock spdl. hole, Morse No. 5 tailstock spdl. taper, 11-5/8" tailstock spdl. travel, 19-1/4"W. bed, 18" 4-jaw chuck, crossslide, steadyrest, chip pan bed
56	1	ENGINE LATHE, DEAN, SMITH & GRACE 21" X 96" , spdl. spds: up to 600 RPM, 4-jaw chuck, chuck guard, tailstock, crossslide, S/N 29399
57	1	LATHE, LODGE & SHIPLEY 20" , 24" swing, 48" centers, spds: 9-500 RPM, (60) thread ranges: 1-64 TPI, (60) fd. ranges: .0037-250 RPM, 2-1/4" hole
58	1	ENGINE LATHE, LODGE & SHIPLEY 14" X 30" , 10" over crossslide, spds: 18-540 RPM, 1-3/4" spdl. hole, L-2 spdl. nose, 10" 3-jaw chuck, fds: 0.0014-0.560 IPR, 6-3/4" tailstock spdl. travel, chip pan bed, tailstock, worklight, S/N 36272
59	1	RAM TYPE TURRET LATHE, LODGE & SHIPLEY MDL. 5W ACME , 17" sw. over bed, 11" sw. over crossslide, 24" chuck face to turret tool holder face, 12" 3-jaw chuck, spdl. spds: 30-406 RPM, 4 pos. horiz. turret on crossslide, 6 pos. rear horiz. hexagonal turret, chip pan bed, S/N 39466 (Note: specifications are approximate)
60	1	MANUAL LATHE, RIVETT 12" X 18" , Mdl. 1020S, 12.5" sw. over bed, 7" over crossslide, (2) spdl. spds: 0-3500 RPM, 1-3/8" spdl. hole, (72) fds: 0.0010-0.060 IPR, (72) thds: 2-120 TPI, 0.04 to 8 mm metric threads, 6.5" 3-jaw chuck, 12.75"W. bed, hyd. tailstock quill, chip pan bed, thread dial, S/N 403
61	1	ENGINE LATHE, LOGAN 12" X 35" , Mdl. 2557V, 12" sw. over bed, 7" sw. over crossslide, 35" dist. btn. centers, spdl. Spds: 40-1400 RPM, 1-3/8" spdl. hole, 8" dia. 3-jaw chuck, 8" dia. 4-jaw chuck, steadyrest, pedestal stand, chuck guard (no tailstock)
62	1	ENGINE LATHE, CLAUSING 12" X 38" , 7" sw. over crossslide, spdl. spds: 52-280 RPM (low range)/360-2000 RPM (high range), 1-3/8" spdl. hole, 3-3/4" tailstock spdl. travel, 49"L. bed, 7-1/4"W. bed, 43-1/2" center height from floor, crossslide (no tool holder), chip pan bed, no chuck, S/N 510876
63	1	PRECISION LATHE, HARDINGE , 13" sw. over bed, 12-1/2" spdl. to turret face, 8 pos. horiz. turret, 12" turret slide long. travel, 4-3/4" turret slide cross travel, 47-1/2" center height from floor, 1.5 HP motor, 5C collet, Bijur manual lube, chip pan bed, high/low spdl. spds. forward/reverse

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
64	1	BENCH LATHE, JET BELT DRIVE 9" X 20" , Mdl. BD-920N, 5-5/16" over crossslide, (6) spdl. spds: 130-2000 RPM, 25/32" spdl. hole, MT 3 taper, 1-1/2 x 8 TPI spdl. mount, 3/4 HP motor, (27) fds: 0.005-0.011 IPR, inch/metric thdng., 1-7/8 compound slide travel, 5" cross slide travel, 16" carriage travel, MT 2 tailstock spdl. taper, 1-9/16" tailstock spdl. travel, 4-1/2"W. bed, steadyrest, followrest, 115 v. 1 ph. pwr., S/N 8065849
65	1	CNC LATHE, FRYER EASY TURN , Touch 2000i CNC control, 18" sw. over bed, 9.25" sw. over crossslide, 40" centers, travels: 10"-X, 37"-Z, 10 HP motor, spds: 50-2500 RPM, 5-station bi-directional automatic tool turret, 10" dia. 3-jaw chuck, tool turret, tailstock, S/N 210131 (See
65A	1	BALANCING MACHINE, STEWART WARNER 10,000 LB. CAP. , Mdl. 2010, 20 – 10,000 lbs. weight cap., 1" to 68" work dia., 7" to 208" work length, 48" dia. max. cap., 10.5" max. trunnion dia. cap., 10 HP motor, horiz. belt driven, (2) stands, (1) std. trunnion/(1) one raise-lower trunnion, walking mech. on L. & R. right col. & drive tower, S/N 363002
65B	1	BALANCING MACHINE, IRD 5,000 LB. CAP. , Mdl. B50, 94" max. dia., 0.16 g. in. max. sensitivity, 0.75"–13" journal dia. range, 5.5"–80" journal to journal separation, 85.5" standard bed length, 49.5" bed extension, balancing spds: 250–6000 RPM, 5 HP motor, underslung belt drive w/manual belt tightening, S/N G23303
66	1	RADIAL ARM DRILL, CARLTON 5' X 15" , drills to center of 120" circle, 15" dia. column, 60" arm length, 39" arm travel on column, 48" head travel on arm, No. 5 MT taper, 18" spdl. travel, (36) spdl. spds: 15–1500 RPM, 12.25" – 60"spdl. center to column, 3.18" spdl. dia., 9"–66" spdl. to base, 65" x 42" base, pwr. head travel, pwr. clamp, pwr. arm elevation, S/N 3A3087
67	1	RADIAL ARM DRILL, SUMMIT 3' X 9" , Mdl. 31H, spds: 70-2350 RPM, 18" x 18" x 18" plain box table, pwr. elevation, S/N 0409
68	1	WELDING POSITIONER, WORTHINGTON 10,000 LB. CAP. , 12" gravity center, 12" eccentricity, 66" table dia., 58" ht. table, table spds: 0–8 RPM, 0-130 deg. table tilt, 3 HP rotation motor, remote pendant, dual pedal foot switch, S/N 37319721
69	1	WELDING POSITIONER , 4-jaw chuck, 3 ph.
70	1	CNC HORIZONTAL MACHINING CENTER, TOYODA MDL. FA450 , Series 15M CNC control, (2) pallets, 17.7" x 17.7", 23.5" X travel, 22" Y travel, 20" Z travel, Cat 40 spdl., spds: 100-10,000 RPM, 30/25 HP motor, 4.9"-24.6" spdl. nose to pallet center, 2"-24" spdl. center to pallet top, 120 tool ATC, S/N NM7759
74	1	CNC VERTICAL GRINDER, CAMPBELL MDL. AS4860-18 , remanufactured & retrofit in 2011, Fanuc 0i-T CNC control, 48" table dia., 60" swing, 20 RPM table spd., 84" horiz. stroke, 18" height under rail, 18" vert. stroke, 10 HP grinding spdl., spds: 1800–7200 RPM, 12" grinding wheel dia., (8) T-slots in table, Fanuc main table drive motor, full C-axis table positioning, 4 pos. grinding wheel changer, auto. dresser, oil chiller, coolant filter & mist collection system, Unisorb Fixator leveling pads, S/N 631-81

LOT	QTY	DESCRIPTION
75	1	HORIZONTAL RIDGID MILL, SUNDRAND 35" X 156" , Mdl. C5U, 35" x 156" table, 120" table cross travel, 36" in/out travel on hard ways, 26" vert. headstock travel, spdl. spds: 14– 1540 RPM, 50 HP motor, overarm pendant control, S/N C5U13 (Note: machine currently disassembled)
76	1	CNC TABLE TYPE HORIZONTAL BORING MILL, LUCAS 6" , Mdl. 40T86, Giddings & Lewis 8000b CNC control, retrofit 2001 by Giddings & Lewis, 6" spdl., No. 50 taper, 36" spdl. travel, spds: 5.6–1120 RPM, fds: 0.005–100 IPM feeds, 60" x 110" table, 96" table cross travel, 72" saddle travel, 72" headstock vert. travel, 210" saddle length, 40 HP motor, new Siemens servo motors w/Simodrive amplifiers, Siemens digital servo motors to all axes, Siemens spdl. motor for headstock, spdl. oil chiller, dual front exit chip conveyors, coolant system, pwr. drawbar, S/N 40T0133
76A	1	AIRLIFT ROTARY TABLE, LUCAS 48" X 72" , 30,000 lb. cap., T-slotted table top, additional precision machined & ground bolt on fixture surface
77	1	TABLE TYPE HORIZONTAL BORING MILL, SELLERS 5" , No. 7 MT taper, 36" spdl. travel, spds: 5.8–334 RPM, fds: 0.003–0.625 IPR, 48" x 88" table, 72" table cross travel, 62" table long. travel, 48" headstock vert. travel, 15 HP motor, Newall 3-axis D.R.O., rapids, thdng.
78	1	HORIZONTAL BORING MILL, GIDDINGS & LEWIS 4" , No. 50 taper, 30" spdl. long. travel, (36) standard range spdl. spds: 10–600 RPM, (7) spdl. spds: 650–1300 RPM (high range), (18) fds: 0.005–0.250 IPR (standard range), (18) fds: 0.002–0.116 IPR (high range), 48" x 74" table, 78" table cross travel, 52" table long. travel, 48" headstock vert. travel, 90"L. bed, 36"W. bed, 8"W. bed ways, 22"W. column, 4"W. column ways, 20 HP motor, pendant control, S/N 150-191-56
79	1	UNIVERSAL VERTICAL GRINDER, SPRINGFIELD MDL. 2A-TR, 25" table dia., 30" swing, 21" grinding head stroke, grinding head fds: 0–120 IPM, table spds: 0–150 RPM, 20" clearance over table, 18" nominal hole depth, 7.5 HP motor, T-slotted face plate type table, (8) T-slots, pendant control, coolant pump, table guard, S/N 56002
80	1	GANTRY CRANE, TVAN 10 T. CAP. (New) , underhung hoist, 22,000 lb. cap., 50' beam length, 157 IPM lift spd., 12' lift ht., 10 HP lift motor, 65 FPM trolley spd., 1.1 HP trolley motor, 46' travel car rail span, 65 FPM travel car spd., 15.7" dia. travel car wheels, dual 2 HP servo drives for gantry traverse, pendant control
81	1	H-FRAME HOIST, 10' x 10', w/Coffing 5 T. cap. chain hoist
82	1	CNC HYDRAULIC POWER SQUARING SHEAR, U.S. INDUSTRIAL 1/4" X 120" , new 2011, Mdl. US1025, 1/4" cap. mild steel, 126" sheet size, 14 SPM, 5.5" throat, 0.75"–36" back gauge adj., 15 HP, 3-axis CNC back gauge control, touch screen operation, squaring arm, pressure sensing hold downs, shadow light, blade guard, S/N J2011-087
83	1	OXY. FUEL/PLASMA BURNER, L-TEC MDL. CM-50-60 CANTILEVER STYLE , L-Tec Mdl. AST optical tracer unit, (2) oxy. fuel burning heads, plasma burning head, twin 48" x 60" pattern tables, no dry burning table, L-Tec Mdl. PCM150 plasma pwr. supply, S/N 92-510-3222

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
84	1	CUTTING MACHINE, LINDE MDL. CM-50 , w/track & table
85	1	MECHANICAL PRESSBRAKE, CHICAGO DREIS & KRUMP 90 T. CAP. , 14-1/2' dist. btn. housings, 3" stroke, 40 SPM, 4" ram adj., 12" die space SDAU, 8" throat, 5 HP motor, 20' die holder, foot treadle
86	1	MECHANICAL PRESS, VERSON 150 T. CAP. , Mdl. B-76-150, 3" stroke, 12" shut height, 5" adj., 30 SPM, 96" x 22" bed, 96" x 17" ram, 7.5 HP motor, S/N 15079
87	1	VERTICAL TURRET LATHE, KING 42" , 42" table dia. w/(3) boring mill jaws, tilting L.H. ram, 5 pos. R.H. ram turret, 4 pos. side head turret, fds: 0.01-0.500, S/N M-42-629
88	1	HYDRAULIC PRESSBRAKE, ADIRA 55 T. CAP. , Mdl. QHD-5020, 4" stroke, 79"L. bed, 61" btn. housings, 12.2" daylight, 5 HP motor, CNC 150 backgauge control, Adiramatic D.R.O. on ram control, S/N 5633/10456
89	1	WELDING TABLE , 6' x 4', H.D., w/Wilton vise
90	1	LOT OF WORKBENCHES : 12' x 3' & 7' x 2-1/2' stainless steel
91	1	LOT OF TOOL & MATERIAL RACKS
92	1	INDUSTRIAL DUST COLLECTOR , 12' x 3' x 2-1/2'
93	1	OVEN, BLUE M MDL. TLG-24-1G-2X , 704 deg. C., 1,333 deg. F., S/N T4-201
94	1	FEED SYSTEM, AUTOMATION , 60 PSI, S/N 7137-3
95	1	CONVEYOR SYSTEM, HYTROL 6- X 1-1/2' , Mdl. H18308-1-1
96	1	GROUT PUMP , portable, skid mtd. self-contained unit, gasoline engine
97	1	BELT SANDER ATTACHMENT, FARROS BLATTER AG MDL. MFK 11 , 4" belt, 15 HP motor, for lathe
98	1	TOOLPOST GRINDER , 5 HP motor, 2" x 18" max. wheel size, H.D.
99	1	TOOLPOST GRINDER, DUMORE , 1 HP motor
100	1	LOT OF TIE-DOWN TOOLING
101	1	LOT OF DRILL SLEEVES
102	1	ROTARY TABLE, 24"
103	1	ROTARY TABLE, 16"
104	1	CHUCK , 24" dia. 4-jaw
105	1	CHUCK , 18" (no jaws)
106	1	CHUCK , 20" dia. 4-jaw
107	1	CHUCK , 16" dia. 3-jaw (one jaw broke)
108	1	WELDING ROTARY TABLE, 30" , motorized, foot pedal, on fixed base
109	1	WELDING TABLE , w/motorized 12" dia. 3-jaw chuck
110	1	WELDING TABLE , w/8" dia. 3-jaw chuck
111	1	TRANSFORMER, ACME , 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary
112	1	TRANSFORMER, ACME , 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary
113	1	TRANSFORMER, ACME , 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary
114	1	TRANSFORMER, ACME , 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary
115	1	TRANSFORMER, ACME , 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
116	1	TRANSFORMER, ACME, 112.5 KVA, 480 v. Delta primary, 480 v./277 v. secondary
117	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
118	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
119	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
120	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
121	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
122	1	TRANSFORMER, WESTINGHOUSE, 112.5 KVA, 480 v. primary, 480/272 v. secondary, V48M47T12E
123	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
124	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
125	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
126	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
127	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
128	1	TRANSFORMER, ACME, 75 KVA, 480 v. Delta primary, 240/120 v. secondary.
129	1	TRANSFORMER, WESTINGHOUSE, 110 KVA, 480 v. primary, 600 v. secondary
130	1	TRANSFORMER, ACME ELECTRIC, 45 KVA, 480 v. primary, 240 v. secondary
131	1	TRANSFORMER, MGM TRANSFORMER CO., 25 KVA, 480 v./240 v./3 ph/60 Hz, 480 v. primary, 240 v. secondary
132	1	TRANSFORMER, GS HEVI-DUTY, 27 KVA, 460 v. primary, 460Y/266 secondary
133	1	TURNING ROLL, VANGUARD 60 METRIC T. (132,000 lbs.) CAP., Mdl. R60-SA, 23.6"– 165.3" work piece dia. range, roller wheel spds: 4–40 IPM, dual 3 HP motors, 15.7" wheel dia., 7.1" width, polyurethane rollers, 440 v./3 ph/ 60 Hz, S/N W1252046
134	1	ADJUSTABLE WELDING TURNING ROLL, ARONSON 10 T. (20,000 lbs.) CAP., Mdl. WRD 20/WRI 10, 6"–156" work pc. dia. range, roller wheel spds: 1–50 IPM, 0.75 HP motor, chain drive, 4 wheel center distances (17", 32", 47", 62"), 13-1/8" wheel center height, 12" wheel dia., 4"W., 110 v./1 ph /60 Hz pwr., S/N 80662
135	1	ADJUSTABLE WELDING TURNING ROLL, ARONSON 10 T. (20,000 lbs.) CAP., Mdl. WRD 20/WRI 10, 6"–156" work pc. dia. range, roller wheel spds: 1–50 IPM, 0.75 HP motor, chain drive, 4 wheel center distances (17", 32", 47", 62"), 13-1/8" wheel center height, 12" wheel dia., 4"W., 110 v./1 ph /60 Hz pwr., (one driver & two idlers), S/N 81677

Clinton Drive Storage Facility Catalog

LOT	QTY	DESCRIPTION
136	1	ADJUSTABLE WELDING TURNING ROLL, ARONSON 10 T. (20,000 lbs.) CAP. , Mdl. WRD 20/WRI 10, 6"–156" work pc. dia. range, roller wheel spds: 1–50 IPM, 0.75 HP motor, chain drive, 4 wheel center distances (17", 32", 47", 62"), 13-1/8" wheel center height, 12" wheel dia., 4"W., 110 v./1 ph /60 Hz pwr., S/N 81693
137	1	LOT CONSISTING OF BOX w/elec. parts, airless pant gun, scrap & FIRE KING FILE CABINET
138	1	AIR COMPRESSOR, LENNOX , 3 ph, S/N 5896H31269
139	1	FORKLIFT, HYSTER 12,000 LB. CAP. , Mdl. S120XMS, new 2005, LPG, 89" triple stage mast, 185" lift height, cushion tires, 42" forks, S/N F004V03664C.
140	1	FORKLIFT, TOYOTA 10,000 LB. CAP. , Mdl. 7FGCU45, new 2011, LPG, 88" triple stage mast, 187" lift height, side shift, cushion tires, 42" forks, S/N 71820
141	1	FORKLIFT, TOYOTA 10,000 LB. CAP. , Mdl. 7FGCU45, new 2011, LPG, 88" triple stage mast, 187" lift height, side shift, cushion tires, 42" forks, S/N 71804
142	1	FORKLIFT, YALE 8,000 LB. CAP. , Mdl. GLC080LJNGAE092, new 2005, LPG, 92" triple stage mast, 185" lift height, side shift, cushion tire, 42" forks, S/N D818V02297C.
143	1	FORKLIFT, TOYOTA 7,000 LB. CAP. , Mdl. 8FGCU32, new 2012, LPG, 88" triple stage mast, 187" lift height, side shift, cushion tire, 42" forks, S/N 17414.
144	1	FORKLIFT, HYSTER 7,000 LB. CAP. , Mdl. S70FT, new 2006, LPG, 95" triple stage mast, 211" lift height, side shift, cushion tires, 42" forks, S/N F187V06610D
144A	1	FORKLIFT, HYSTER 5,000 LB. CAP , Mdl. S50FT, new 2011, LPG, 83" triple stage mast, 189" lift height, side shift, cushion tire, 42" forks, S/N F187V19736J
145	1	FORKLIFT, YALE 5,000 LB. CAP. , Mdl. GLC050VXNVSE088, new 2007, LPG, 88" triple stage mast, 201" lift height, side shift, cushion tires, 42" forks, S/N A910V09425E.
146	1	FORKLIFT, YALE 5,000 LB. CAP. , Mdl. GLC050VXNVSE085, new 2006, LPG, 85" triple stage mast, 195" lift height, side shift, cushion tires, 42" forks, S/N A910V06530D.
147	1	FORKLIFT, HYUNDAI 3,500 LB. CAP. , Mdl. HLF18-5, new 2007, LPG, 83" triple stage mast, 189" lift height, side shift, cushion tires, 42" forks, S/N FN02100009.
148	1	PALLET JACK, HYSTER 4,000 LB. CAP. , Mdl. W40Z, new 2008, 27" x 48", w/battery, S/N B218N15684F
149	1	PALLET JACK, HYSTER 4,000 LB. CAP. , Mdl. W40Z, new 2007, 27" x 48", w/battery, S/N B218N14425E.
150	1	TOW TRACTOR, HARLAN 3,000 LB. CAP. , Mdl. HTAG30, LPG, 3,000 lb. drawbar pull, 859 H.O.M.