

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
1	1	<b>MAGNETIC BASE DRILL, FMT MDL. 303012</b> , 110 v., w/carrying case, S/N N27813 (Location D)
2	1	<b>PUNCH SET, GREENLEE MDL. 7306SB SLUG BUSTER</b> , knock-out punch & hyd. Driver set for 1/2" to 2" conduit, w/carrying case (Location D)
3	1	<b>ROTARY HAMMER, INDUSTRIAL MDL. 143384</b> , w/carrying case (Location D)
4	1	<b>PORTA BANDSAW, MILWAUKEE MDL. 6239</b> , w/carrying case (Location D)
5	1	<b>LOT OF DEWALT RECHARGEABLE DRILL &amp; NUT DRIVE</b> , 18 v., w/(2) charging stations & batteries, DeWalt portable flashlight, carrying case (Location D)
6	1	<b>LOT OF DEWALT RECHARGEABLE DRILL &amp; NUT DRIVE</b> , 18 v., w/(2) charging stations & batteries, DeWalt portable flashlight (Location D)
7	1	<b>LOT OF LABELING MACHINES</b> , including: IDXPRT hand-held labeler, 3M Mdl. PL100 labeler, Brother P-Touch portable labeler w/carrying case (Location D)
8	1	<b>ELECTRONIC CHARGING SCALE</b> , Mdl. 9010 (Location D)
9	1	<b>TRISTAND, RIDGID MDL. 460</b> , 1/2" to 6" cap. (Location D)
10	1	<b>LARGE ADJUSTABLE WRENCH, EXTRA 24"</b> (Location D)
11	1	<b>LARGE ADJUSTABLE WRENCH, EXTRA 24"</b> (Location D)
12	1	<b>SEGMENTED BREAK-OUT WRENCH</b> , 3" cap. (Location D)
13	1	<b>CONDUIT BENDER</b> , 7/8" O.D., 3-1/4" R (Location D)
14	1	<b>CIRCULAR SAW, SKILSAW MDL. 5485</b> , 2.3 HP motor, 13 amp (Location D)
15	1	<b>BENCH GRINDER, RYOBI 6"</b> , w/extra abrasives (Location D)
16	1	<b>ABRASIVE CHOP SAW, RIDGID</b> , w/extra blades (Location D)
17	1	<b>FINGERBRAKE, 48"W.</b> , 58" x 46" surface area, large cap. Workforce vise on
18	1	<b>SLITTER, WILDER MACHINERY SERIES WILDER WORKHORSE MDL. 1624</b> , 18 ga. mild steel, infeed/outfeed table, S/N 46221 (Location D)
19	1	<b>WORKTABLE</b> , 36" dp. X 60"L., 2-tier, built-in drawers, H.D., caster mtd. (Location D)
20	1	<b>ROLLING WORKTABLE</b> , 46" x 60" surface, 2-tier (Location D)
21	1	<b>SHOP FAN, MAXXAIR 42"</b> , round (Location D)
22	1	<b>SHOP FAN, MAXXAIR 42"</b> , round (Location D)
23	1	<b>LOT OF BANDING CART, SIGNODE MDL. DF-15</b> , w/banding tools & clips (Location D)
24	1	<b>LOT OF SHOP VACUUMS</b> : Ridgid 16 gal. cap. & Stinger Pony Vac (Location D)
25	1	<b>PORTABLE HEATER, DAYTON</b> , 175,000 BTU's, oil fired (Location D)
26	1	<b>PORTABLE WELDER/GENERATOR, MILLER BOBCAT MDL. 250</b> , CC/CV, AC/DC welder, 10,500 watt generator, gasoline pwr., S/N LH080819H (Location D)
27	1	<b>WELDING MACHINE, LINCOLN IDEALARC MDL. R3R-400</b> , new 2005, Lincoln TIG Module, leads, some welding wire & stick, S/N U1050607032 (Location D)
28	1	<b>PLASMA CUTTER, THERMAL DYNAMICS MDL. CUTMASTER 51</b> , new 2005, torch, 208/230 VAC, (Location D)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
29	1	<b>TORCH CART</b> , pneu. tires, w/torch hose, gauges & accessories (Location D)
30	1	<b>LOT OF WELDING &amp; CUTTING SUPPLIES</b> , including: welding cabinet w/torches, gauges, hard hats, gloves, mask, welding hoods on top & hanging on wall (Location D)
31	1	<b>LOT OF MISC. SHOP TOOLS</b> , including: Spirit levels, T squares, tin snips, safety harnesses, etc. (Location D)
32	1	<b>ROLLING TOOL CABINET</b> , w/drawers (Location D)
33	1	<b>ROLLING TOOL CABINET</b> , w/drawers (Location D)
34	1	<b>LOT OF SCREW TYPE HELPER STANDS (4)</b> , RIDGID (unused) (Location D)
35	1	<b>LOT OF HELPER STANDS (6)</b> (Location D)
36	1	<b>RECIPROCATING TYPE AIR COMPRESSOR, HUSKY</b> , 2-stage, 7 HP motor, 80 gal. vert. air receiver (Location D)
37	1	<b>CNC WATERJET CUTTING MACHINE, I.W.M. 6' X 13' CUTTING CAP.</b> , new 2012, Mdl. WC4WA4020UB, 8' x 14' material table, 55,000 PSI Mdl. W1P5H intensifier pump S/N DWP0106056, 3.5L/min, XL Mdl. 1534 oil chiller, IMW auto. abrasive delivery system, up to 4" thk. metal cutting cap., less than 400 hrs. total use, P.C. based control system., UNDER POWER, S/N N.A. (Location D)
38	1	<b>CNC HYDRAULIC PRESSBRAKE, CINCINNATI 350 T. X 16'</b> , Mdl. 350 FMII X 14', Cincinnati FORM MASTER II CNC control, 16' overall bed length, 14' dist. btn. housings, 10" max. stroke, 11" throat, 5.75"W. bed, front bolt-on material suppts, UNDER POWER, S/N 47710 (Location D)
39	1	<b>4-WAY VEE DIE</b> , 194"L. (Location D)
40	1	<b>LOT OF 86"L. 4-WAY VEE DIE &amp; ASSORTED PUNCHES</b> (Located in machine) (Location D)
41	1	<b>4-WAY VEE DIE</b> , 81-3/4"L. (Location D)
42	1	<b>4-WAY VEE DIE</b> , 48"L. (Located in machine) (Location D)
43	1	<b>PUNCH &amp; DIE SET</b> , 194-1/2"L. (Location D)
44	1	<b>PUNCH &amp; DIE SET</b> , 194"L. die, 192"L. punch (Location D)
45	1	<b>PUNCH &amp; DIE SET</b> , 170"L. (Location D)
46	1	<b>BOTTOM VEE DIE</b> , 194"L. x 5"W. (Location D)
47	1	<b>BOTTOM VEE DIE</b> , 120"L. (Location D)
48	1	<b>A-FRAME ROLLING DIE RACK</b> , w/numerous assorted dies (Location D)
49	1	<b>LOT OF PUNCH DIES</b> (on one pallet) (Location D)
50	1	<b>LOT OF PUNCH DIES</b> (on one pallet) (Location D)
51	1	<b>LOT OF PUNCH DIES &amp; ASSORTED BOTTOM VEE DIES</b> (Location D)
52	1	<b>LOT OF VEE DIES &amp; ROUNDING DIES</b> (Location D)
53	1	<b>CONTAINER</b> , w/bottom Vee dies & (1) punch die (Location D)
54	1	<b>LOT OF RAW MATERIAL</b> : copper pipe, allthread, PVC pipe (on wall rack, in assorted boxes & on floor in front) (Location D)
55	1	<b>LOT OF ELECTRICAL WIRE ON ONE PALLET &amp; ADDITIONAL WIRE DISPENSING RACKS</b> (Location D)
56	1	<b>LOT OF RAW MATERIAL</b> : 5' x 12' sheets (3), A36 carbon steel (Location D)
57	1	<b>LOT OF RAW MATERIAL</b> : 4' x 10' sheets (4), stainless steel, assorted thicknesses (Location D)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
58	1	<b>LOT OF RAW MATERIAL:</b> carbon steel plate, assorted thicknesses (Location D)
59	1	<b>LOT OF ASSORTED SCRAP MATERIAL:</b> misc. drops (stainless steel, aluminum & carbon steel), pipe, tube stock, pipe couplings (Location D)
60	1	<b>LOT OF RAW MATERIAL,</b> w/rolling raw material storage rack (Location D)
61	1	<b>ELECTRICAL TRANSFORMER, ACME MDL. T-3-53342-3S,</b> 30 KVA, 480 Delta Primary, 240D/120 secondary, 3 phase, dry type (Location D)
62	1	<b>LOT OF ELECTRICAL DISCONNECTS (2), GENERAL ELECTRIC, H.D.,</b> rated @ 60 amp/240 v., switch gear & 4-conductor plugs w/heavy electrical cable (Location D)
63	1	<b>LOT OF COMPRESSED GAS CYLINDERS &amp; ROLLING CYLINDER STORAGE RACK</b> (Location D)
64	1	<b>LOT OF PALLET RACK SECTIONS (2),</b> 7' ht. x 8'W. x 38" dp. x 2-tier, metal shelf inserts (Location D)
65	1	<b>LOT OF ELECTRICAL CORDS</b> (Location D)
66	1	<b>LOT OF COLLAPSABLE STORAGE BASKETS (8),</b> w/contents (Location D)
67	1	<b>ELECTRICAL TRANSFORMER, MGM TRANSFORMER CO. SYSTEM 220-1,</b> 3 phase taps (Location D)
68	1	<b>LOT OF CLEANING SUPPLIES, ASSORTED ADHESIVES, PAINT</b> (Located in shelf unit) (Location D)
69	1	<b>LOT OF STEP LADDERS:</b> (1) 8' & (1) 6' (Location D)
70	1	<b>FORKLIFT, YALE 5,000 (est.) LB. CAP.,</b> Mdl. D42408, LPG engine, 4-stage mast, cushion tires, 6'L. forks, extra set of 42"L. forks, fork positioner, 15,130 H.O.M., S/N 5021352-05 (Location D)
71	1	<b>HYDRAULIC PALLET JACK,</b> 4,000 (est.) lb. cap. (Location D)
72	1	<b>LOT CONSISTING OF (1) SET OF (2) MACHINERY SKATES, HEVI-HAUL MDL. SD-50,</b> 25 T. cap. ea., S/N 23184 (Location D)
73	1	<b>LOT OF OFFICE FURNITURE:</b> executive desk, matching credenza, executive chair (approx. one year old) (Location D)
74	1	<b>LOT OF RECEPTION AREA FURNITURE:</b> entry way curved front knotty pine reception desk, (6) cushion guest chairs, lamp, artwork (Location D)
75	1	<b>LOT OF BREAKROOM APPLIANCES:</b> Sanyo miniature refrigerator, microwave oven, Home Depot Igloo cooler (Location D)
77	1	<b>LOT OF ELECTRIC MOTORS (4), BALDOR RELIANCE MDL. EM7020T-1,</b> 60/50 Hz, XPF enclosure, 3 phase, 1.5/1 HP motor, 230/460/190/380 v., 11/65 / 970 RPM, 75 C rise, Spec 36J694S916G1 (unused) (Location D)
78	1	<b>LOT OF ELECTRIC MOTORS (3), BALDOR RELIANCE MDL. EM7020T-1,</b> 60/50 Hz, XPF enclosure, 3 phase, 1.5/1 HP, 230/460/190/380 v., 11/65 / 970 RPM, 75 C rise, Spec 36J694S916G1 (unused) (Location D)
79	1	<b>ELECTRIC MOTOR, MARATHON,</b> 1/2 HP, 1,140 RPM, 230/460 v., 3 phase, 60 Hz, Frame 506Z (unused) (Location D)
80	1	<b>ELECTRIC MOTOR, BALDOR RELIANCE,</b> 60 Hz, TEFC enclosure, 3 phase, 1-1/2 HP, 280/230/460 v., 1,740 RPM (unused) (Location D)
81	1	<b>ELECTRIC MOTOR, MARATHON MDL. G651,</b> 1/3 HP, 1,725 RPM, 115/203/230 v., sgl. Phase, 60 Hz, Frame 56, explosion proof, rigid base, 6.6/3.1-3.3 amps (unused) (Location D)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
82	1	<b>ELECTRIC MOTOR, MARATHON MDL. 8VH56T/1T5560A P</b> , FR-562-80, 3 phase, Type TS, continuous duty, 60 Hz, 1/2 HP, 1,140 RPM, 230/460 v. (unused) (Location D)
83	1	<b>ELECTRIC MOTOR, MARATHON MDL. 056C11G5306</b> , 1/4 HP, 1,140 RPM, 115/208/230 v., sgl. phase, 60 Hz, explosion proof, Frame 56, rigid base, 6.5/3.1-3.4 amps (unused) (Location D)
84	1	<b>LOT OF ELECTRIC MOTORS (2), A.O. SMITH MDL. F48F68861</b> , 1/4 HP, 1,100 RPM, 2-spd., 208/230 v., 60/50 Hz, Frame 48Y, sgl. phase, Type UE, 2-1/2 amps (unused) (Location D)
85	1	<b>LOT OF ELECTRIC MOTORS (5), MARATHON MDL. F6T17F5303</b> , 1-1/2 HP -1, 1,725/1,425 RPM, 208/230/460/190/380 v., 3 phase, 60/50 Hz, Frame 56H, TEFC enclosure, rigid base, 4.8/4.8/2.4/4.2/2.1 amps (unused) (Location D)
86	1	<b>ELECTRIC MOTOR, BALDOR MDL. 031-P-508</b> , 60 Hz, TEFC enclosure, 3 phase, 1-1/2 HP, 230/460 v., 1,140 RPM (unused) (Location D)
87	1	<b>ELECTRIC MOTOR, BALDOR MDL. 031-P-508</b> , 60 Hz, TEFC enclosure, 3 phase, 1-1/2 HP, 230/460 v., 1,140 RPM (unused) (Location D)
88	1	<b>ELECTRIC MOTOR, BALDOR MDL. CM7006-50</b> , 60 Hz, XPFC enclosure, 3 phase, 1/2 HP, 220/380/440 v., 1,425 RPM (unused) (Location D)
89	1	<b>LOT OF ELECTRIC MOTORS (2), BALDOR MDL. L4006A</b> , 60 Hz, XPFC enclosure, sgl. Phase, 1/3 HP, 115/208/230 v., 1,725 RPM, Spec: 34-5426-5597 (unused) (Location D)
90	1	<b>LOT OF MISC. ELECTRIC MOTORS</b> , (3) Fasco, dual shaft, 1/3 HP/460 v., 1,075 RPM & (1) Baldor (Location D)
91	1	<b>LOT OF ELECTRICAL SWITCHGEAR</b> : Square D, Cutler Hammer & Siemens, electrical shutoff (Location D)
92	1	<b>LOT OF ELECTRICAL SWITCHGEAR</b> : Square D, ABB & Hammond Mfg.
93	1	<b>LOT CONSISTING OF RETURN &amp; SUPPLY AIR CONDITIONING GRILLS FOR WALL UNITS</b> (Location D)
94	1	<b>SERVO DRIVE</b> , Danfoss Model VLT 6000 HVAC Servo Drive 5.5KW 7.5HP (Location D)
95	1	<b>SERVO DRIVE</b> , Danfoss Model VLT 6000 HVAC Servo Drive 5.5KW 7.5HP (Location D)
96	1	<b>SERVO DRIVE</b> , Danfoss Model VLT 6000 HVAC Servo Drive 5.5KW 7.5HP (Location D)
97	1	<b>SERVO DRIVE</b> , Danfoss Model VLT 6000 HVAC Servo Drive 5.5KW 7.5HP (Location D)
98	1	<b>MOTOR CONTROL, ABB</b> (Location D)
99	1	<b>LOT OF AC SERVICE SUPPLIES</b> (Location D)
100	1	<b>LOT OF COPPER FITTINGS</b> (Location D)
101	1	<b>LOT OF TEMPERATURE CONTROL ACCESSORIES</b> : high heat thermostats, humidstats, standard thermostats, lead lag controller (Location D)
102	1	<b>LOT OF LOGIC CONTROLLERS &amp; RELAYS</b> : Siemens, Sola & Altivar (Location D)
103	1	<b>LOT OF PHASE MONITOR TYPE POWER CONTROLLERS, RELAYS, TRANSFORMERS, CIRCUIT BREAKERS, FUSE HOLDERS</b> (Location D)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
104	1	<b>LOT CONSISTING OF APPLETON &amp; KILLARK SWITCHGEAR; DWYER EXPLOSION PROOF MI CABLE; COLORATECH EXPLOSION PROOF HEAT THERMOSTAT; PRESSURE SWITCHES; APPLETON SEALANT FOR EXPLOSION PROOF FIXTURES</b> (Location D)
105	1	<b>LOT OF LARGE QUANTITY OF APPLETON EXPLOSION PROOF FITTINGS &amp; BOXES</b> (Location D)
106	1	<b>LARGE EXPLOSION PROOF ENCLOSURE, KILLARK QUANTUM EXB12186, S/N 34000</b> (Location D)
107	1	<b>PALLET OF APPLETON EXPLOSION PROOF PRODUCTS, Mdl. ST-90200 connectors, Mdl. ST-45200 connectors, ELBY-75, ST-9075, ST-200 connectors, and other misc.models.</b> (Location D)
108	1	<b>PNEUMATIC CYLINDERS, (2) FLAIRLINE Mdl. TC 2-1/2 X 24 HC MP2, (5) smaller Flairline cylinders, mounting hardware</b> (Location D)
109	1	<b>LOT OF RUBBER DRIVE BELTS AND SHEAVES</b> (Location D)
110	1	<b>LOT OF TRUCKERS TIE DOWN STRAPS AND COME-ALONGS</b> (Location D)
111	1	<b>LOT OF LARGE QUANTITY OF HARDWARE IN PIDGEON HOLE CABINET</b> (including on top & in front) (Location D)
112	1	<b>LOT OF LARGE QUANTITY OF HARDWARE IN PIDGEON HOLE CABINET</b> (including on top & in front) (Location D)
113	1	<b>AIR CONDITIONING SYSTEM, EUBANK MDL. V436B05A1FDS-NW2 HIGH EFFICIENCY, 3 T. cap., 208/230 v., sgl. phase, 60 Hz, wall mtd., w/grills on top</b> (unused) (Location D)
114	1	<b>LOT OF EXPLOSION PROOF AND STANDARD HEATER ELEMENTS</b> (Location D)
115	1	<b>REFRIGERANT, Dupont SUVA410A, (1) full and (1) partial container</b> (Location D)
116	1	<b>REFRIGERATION COMPRESSOR, Danfoss, with insulated tubing</b> (Location D)
117	1	<b>LOT OF: BI fans, fan blades, exhaust fans, plenums</b> (Location D)
118	1	<b>LOT OF EXHAUST FANS (3), S&amp;P MDL. TD-800/200 MIXVENT</b> (Location D)
119	1	<b>LOT OF COIL CLEANER, TEXAS NATIONAL INC MDL. COIL LITE</b> (in one barrel) (Location D)
120	1	<b>LOT OF ELECTRI-FLEX MDL. AQUATITE COAX COVER</b> (on one spool) (Location D)
120A	1	<b>LOT OF ELECTRICAL SUPPLIES: conduit, electrical connectors, I.D. tags, etc.</b> (Location D)
121	1	<b>LARGE CAPACITY CNC HOLLOW SPINDLE LATHE, AMERICAN 46" X 180"</b> , retrofitted in 2012 with NCT Automation Model NCT201T LCD touch screen CNC control system (FANUC compatible programming, LADDER program, WINDOWS op. sys., EtherCAT, HEIDENHAIN EnDat 2.2 interface for measuring, (4) USB connections, remote diagnostics, built-in oscilloscope), 12.5" spdl. hole, 46" sw. over bed, 26" sw. over carriage, 6-station tool turret, 40"W. bed, front & rear Cushman 24" dia. 4-jaw chucks, hardened & ground ways, 75 HP DC motor w/transformer, UNDER POWER, S/N 80731/81 (Location A)
122	1	<b>HYDRAULIC STEADYREST, Mdl. AT50700</b> (Location A)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
123	1	<b>LARGE CAPACITY VERTICAL HONE, MICROMATIC MDL. 15V65</b> , 12" max. dia, 65" max. stroke, sgl. spd., dual 10" x 12" shuttle tables, Trabon Mdl. WSC lubrication, outboard hyd. system, S/N 100 (Location A)
124	1	<b>HYDRAULIC PLATE SHEAR, ATLANTIC ½" X 10'</b> ., Mdl. HDS10.1/2, front mounted digital control, backgauge, 2' squaring arm, S/N 20813 (Location B)
125	1	<b>LARGE CAPACITY HYDRAULIC SURFACE GRINDER, THOMPSON 36" X 240"</b> , 36" x 240" table, 48" under grinding wheel, 30 HP motor, (5) 36" x 48" magnetic chucks, 6"W. x 20" dia. wheel, auto power downfeed, S/N N.A. (Location C)
126	1	<b>TABLE TYPE HORIZONTAL MILLING/BORING MACHINE, WOTAN 5-1/8"</b> , Mdl. B130L, 5-1/8" spd., No. 6 MT, 35" spd. travel, (33) spd. spds.: 2.5–1000 RPM, (27) fds: 0.0013–0.500 IPR, 60" x 118" table, 108" table cross travel, 75" long. travel, 70" headstock vert. travel, 112 IPM rapids, 183" saddle, 25 HP motor, Pratt & Whitney 50" pwr. rotation table, 28" facing head, Sony 3-axis D.R.O., right angle head, spd. suppt., outriggers, thdng., pendant, misc. tooling, S/N 54348 (Location E)
127	1	<b>TABLE TYPE HORIZONTAL MILLING/BORING MACHINE, UNION 5"</b> , Mdl. BFT125/5, 5" spd., Metric 80 taper, spds: 3.55-710 RPM, 39" spd. travel, 63" table cross travel, 63" vert. headstock travel, 55" x 63" table, 17,600 lbs. table load cap., 23 HP motor, pendant, 31" built-in facing head, rotary table, outboard suppt., way covers on X, S/N 8662/66 (Location E)
128	1	<b>POWER ROTARY TABLE WITH INFEED, GIDDINGS &amp; LEWIS 120" X 120"</b> , 50 T. table load, (9) T-slots, 48" ht. table, 144"L. runway, 48" table travel on bed, 84"W. bed, ½ deg. graduations, 10 HP AC feed & rapid traverse., hand crank for fine feed & adj., portable push-button station, S/N N.A. (Location E)
129	1	<b>JIG MILL, DEVLIEG 3"</b> , Mdl. 3K-72, 3" spd., No. 40 taper, (16) spd. spds: 17-1660 RPM, (16) spd. fds: 0.0013-0.167 IPR, 45" x 72" table, 16" spd. travel, 72" X-axis travel, 60" Y-axis travel, 16" table retract, rapids, pwr. drawbar, stainless steel way covers, S/N 9367 (Location E)
130	1	<b>VERTICAL BORING MILL, MORANDO 67"</b> , Mdl. VS17, 67" table w/(4) boring mill jaws, 75" swing, 74" under rail, 170 RPM, 65 HP motor, (2) swivel ram heads, side head, coolant, rapids, pwr. rail elevation, pwr. clamping, pendant, upgraded electric, lft. ram eqpd. w/grinding spd. & added fds. w/grinding spd. controls on pendant, S/N 05226 (Note: Loading charge of \$1500.00 will apply to this item. This machine may require transportation Permits due to size or weight. All Permits are the buyer's responsibility) (Location E)
131	1	<b>BED TYPE VERTICAL MILL, CINCINNATI MILACRON MDL 450-20 VERCIPOWER</b> , 20" x 86.5" table, 42" long. travel, 18" cross travel, 24" vert. travel, (24) spd. spds: 14-1400 RPM, No. 50 taper, 2" to 26" spd. to table, (32) feeds, 3/8 – 90 IPM long., 3/16 – 45 IPM cross, 50 HP motor, rapids, S/N 331045V75-0002 (Location E)
132	1	<b>PLAIN HORIZONTAL MILL, KEARNEY &amp; TRECKER MDL 430TF17 WITH MOTORIZED OVERARM</b> , 17" x 80" table, 42" long. travel, 14" cross travel, 18" vert. travel, (24) main spd. spds: 15–1500 RPM, (8) ram spd. spds: 100–1600 RPM, No. 50 taper, (32) fds, 3/8–90 IPM long & cross, 1/8 – 30 vert., 30 HP motor, twin elevating screws, ram type motorized overarm, rear controls, coolant pump, rapids, S/N 4-7451 (Location E)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
133	1	<b>PLAIN HORIZONTAL MILL, KEARNEY &amp; TRECKER MDL 430TF17 WITH MOTORIZED OVERARM</b> , 17" x 94" table, 42" long. travel, 14" cross travel, 18" vert. travel, (24) main spdl. spds: 15–1500 RPM, (8) ram spdl. spds: 100–1600 RPM, No. 50 taper, (32 fds.) 3/8 – 90 IPM long & cross, 1/8 – 30 vert., 30 HP motor, twin elevating screws, ram type motorized overarm, rear controls, coolant pump, rapids, S/N 4-7275 (Location E)
134	1	<b>PLAIN HORIZONTAL MILL, KEARNEY &amp; TRECKER MDL 425TF</b> , 17" x 88" table, 42" long. travel, 14" cross travel, 18" vert. travel, (24) spdl. spds: 13–1300 RPM, No. 50 taper, (32) fds: 3/8–90 IPM, 25 HP motor, twin elevating screws, dbl. overarm, rear controls, coolant pump, rapids, S/N 7-8233 (Location E)
135	1	<b>MECHANICAL SHEAR, CINCINNATI 12' X 3/4"</b> , Mdl. 6212, 144" x 3/4" cap. in mild steel, 30 SPM, 600 RPM flywheel, 65" front gauge, 36" backgauge, 39 T. cap. hold-down press., 1/2" per ft. rake angle, 147" dist. btn. housings, 32" ht. table, 20" projection below floor, 1-1/16" ram adj., 18" throat, 30 HP motor, front operated backgauge, 12' squaring arm, includes (8) 12'-5" shear knives, 12' -5" length, 4-3/4" width, 1-1/8" to 1-3/8" thickness, S/N 28239 (Note: Loading Charge of \$1,500.00 will apply to this item. This machine may require transportation Permits due to size or weight. All Permits are the buyer's responsibility) (Location E)
136	1	<b>HYDRAULIC SHEAR, PACIFIC 10' X 3/4"</b> , Mdl. 750-S10A, 10' x 3/4" cap. @ 1/2" per ft. rake, 10' x 1" cap. @ 3/4" per ft. rake, 124" knives, 10'-3" dist. btn. housings, 18" gap, (11) hold-downs, 33 T. cap. hold-down press, 40 HP motor, front operated backgauge, adj. stroke, adj. rake angle, adj. knife clearance, squaring arm, S/N S10141 (Note: Loading Charge of \$1,500.00 will apply to this item. This machine may require transportation Permits due to size or weight. All Permits are the buyer's responsibility) (Location E)
137	1	<b>ENGINE LATHE, AXELSON 22" X 150"</b> , 15" sw. over crossslide, (24) spdl. spds: 13-1577 RPM, (54) fds: 0.0027–0.1655 IPR, (54) thds: 1-1/2-92 TPI, 10-5/8" crossslide travel, 4-3/4" comp. rest travel, 2-7/8" tailstock spdl. dia., 9" tailstock spdl. travel, No. 4 MT tailstock spdl. taper, 15" dia. 4-jaw chuck, 15 HP motor, taper attach., (3) steadyrests, hard ways, thread dial, tailstock, coolant, S/N 4576 (Location E)
138	1	<b>HOLLOW SPINDLE LATHE, LANSING 28" X 60"</b> , 9.25" spdl. hole, 18.875" over crossslide, 37.75" swing in gap, 17" gap length, 60" dist. btn. centers, (16) spdl. spds: 8–500 RPM, D1-15 Camlock spdl. nose, 20"W. bed, 25 HP motor, inch/metric thdng., tailstock, taper attach., followrest, chip pans, coolant, S/N 38381 (Location E)
139	1	<b>RADIAL DRILL, CARLTON 10' X 26" WITH 36" EXTRA HEIGHT</b> , drills to center of 240" circle, 26" dia. column, 120"L. length, 91.5" arm travel on column, 104" head travel on arm, No. 6 MT taper, 24" spdl. travel, (36) spdl. spds: 12–1200 RPM, 16.5"–120" spdl. center to column, 20.5"–136" spdl. to base (36" extra), 34"–138" spdl. radius, 25 HP motor, no base, pwr. head traverse, pwr. clamping, pwr. arm elevation, S/N 5A3572 (Location E)
140	1	<b>RADIAL DRILL, CARLTON 6' X 19" WITH 24" EXTRA HEIGHT</b> , drills to center of 144" circle, 19" dia. column, 72"L. arm, 46" arm travel on column, 59" head travel on arm, No. 6 MT taper, 20" spdl. travel, (36) spdl. spds: 15–1500 RPM, 13.25"–72" spdl. center to column, 4" spdl. dia., 32"–102" spdl. to base, 77" x 50" base, pwr. head travel, pwr. clamping, pwr. arm elevation, S/N 4A4956 (Location E)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
141	1	<b>RADIAL DRILL, CARLTON 5' X 15"</b> , drills to center of 120" circle, 15" dia. column, 60"L. arm, 39" arm travel on column, 48" head travel on arm, No. 5 MT taper, 18" spdl. travel, (36) spdl. spds: 15–1500 RPM, 12.25"–60" spdl. center to column, 3.18" spdl. dia., 9"–66" spdl. to base, 65" x 42" base, pwr. head travel, pwr. clamping, pwr. arm elevation, S/N 3A3087 (Location E)
142	1	<b>CNC 6-AXIS FLOOR TYPE HORIZONTAL GUN DRILL, TECHNIDRILL MDL. 200-2.0-48-5A-CNC</b> , 6-axis CNC control, 0.1875"–2" drill dia. range, 48" Z-axis drill stroke w/(2) whip guides, 146" X-axis column travel, 36" Y-axis vert. column travel, 146" x 48" T-slotted set-up table, 40,000 lb. cap., (2) spd. ranges: 600–6000 RPM, 20 HP spdl. motor, high-flow coolant system, ABB spdl. drive, (2) 48" sq. pwr. index rotary tables, chip conveyor, S/N 7120 (Location E)
143	1	<b>ROTARY SURFACE GRINDER, SULMECANICA 39"</b> , Mdl. RAPG-100, 39.4" table, 1,700 lbs. cap., (3) table spds: 10, 20 & 30 RPM, 11.8" max. grinding height, 19.7" dia. segmented wheel, (8) segments, 13.4 IPM rapid downfeed, 0.0001" min. hand wheel div., 60 HP motor, Marposs E5 inprocess gauging, coolant filter system, mist buster, wheel dresser, S/N 1111 (Location E)
145	1	<b>LARGE CAPACITY OVERHEAD BRIDGE CRANE, P&amp;H 150/50 T. X 86' SPAN X 53' LIFT HT.</b> , dbl. girder, 150 T. main cap., 50 T. aux. cap., 13'6" spread, 7'3" min. dist. btn. hooks, 42" dia. x 126" long main hoist drum, 125 HP main motor, 75" center to center of wheels, lft. hand cab loc., S/N C14311/C18851 (Note: Loading charge of \$5,000 will apply to this item. This machine may require transportation Permits due to size or weight. All Permits are the buyer's responsibility) (Location E)
146	1	<b>CNC LATHE, MAZAK MDL. INTEGRIX 30</b> , Mazatrol T-Plus CNC control, 12" hyd. chuck, 20" max. sw. over bed, 15.75" max sw. over carriage, 40.5" centers, 3.46" hole, spds: 35-3500 RPM, 35 HP motor, No. 40 taper, 40 pos. ATC, under power, S/N 185484 (Location F)
147	1	<b>ELECTRONIC DISCHARGE MACHINE, MITSUBISHI MDL. V55F SINKER RAM TYPE</b> , Mitsubishi C11V70 CNC control, 16 pos. 3R ATC, "C" axis programmable, 51" x 30" x 22" tank, S/N 045V11563 (Location F)
148	1	<b>ROUGH TERRAIN HYDRAULIC TELESCOPING CRANE, GALION 15 T. CAP.</b> , Mdl. 150A, 4-section boom, diesel engine, outriggers, good rubber, UNDER POWER (Location F)
149	1	<b>VACUUM PUMP LIQUID EXTRACTION RING PACKAGE, INCLUDES:</b> GARDNER DENVER 7" SERIES CYCLO-BLOWER, 1,265 cu. ft./min, rated to vertically vacuum liquid mercury up to 24" Hg, gauged for -30" Hg. (Part #7CDL11H), a 3" & 4" outflow Kunkle relief valve, 30 HP explosion proof GE 3 ph motor, 7" PrdGenTex silencer, 7" Solberg air/water stripper w/2.25" valved breather; <b>THE SOIL VAPRO EXTRACTORY SYSTEM INCLUDES:</b> Ejector Systems 750 gal. tank w/4" effluent intake, 3" & 4" outflows, carbon fiber block filter, secondary 10 HP channel blower, (2) 100 gal yellow water flush tanks, 10 HP A.O. Smith elec. motor, Leeson XP water pump; <b>LIQUID RING VACUUM PUMP INCLUDES:</b> L.R.V. tank, jet blower intake, (2) 3 HP XP auger motors on base of liquid-gas stripper. Sold as a package with CON-EX CONTAINER AND ALL WIRING, BREAKERS, CONTROL PANEL & LIGHTS. (Location G)



<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
150	1	<b>HYDRAULIC PRESSBRAKE, PACIFIC 90 T. X 10'W.</b> , Mdl. 90x10, 10" throat, 104" dist. btn. housings, 460 V/3PH, UNDER POWER, S/N 5322 (Note: needs minor electrical work) (Location H)
151	1	<b>MECHANICAL UNIVERSAL TYPE IRONWORKER, BUFFALO MDL. 1-1/2 DUAL OPERATION</b> , 65 T. cap., 5 HP, foot treadle & hand lever controls, under power, S/N N.A. (Location H)
152	1	<b>CUT-TO-LENGTH LINE, WYSONG 16 GA. X 4'W. X 10'L. SHEETS</b> , (2) adj. width coil spools max width 50", 4'W. straightening rolls, 16 ga. x 4' shear, 12" exit rubber belt w/dual roller conveyor, auto control side panel, S/N N.A. (Location H)
153	1	<b>RARE ANTIQUE AUTOMOBILE, 1926 OAKLAND 4-DOOR SPORT PHACTON</b> , body by Holdens, collapsible rag top, seats 5, 6-cyl. engine, spare tire, 1 of only 3 produced in 1926 for export, right hand drive, original engine: rebuilt, original drive line: rebuilt, crystal glass, opera seats, blue body, black fenders, original owner's manual & maintenance manual included (Note: Owner believes this is the last one of its kind left in the world. Rag top has obvious weathering & wear. Running condition) (Location H)
154	1	<b>LARGE CAPACITY FORKLIFT, CATERPILLAR 30,000 LB. CAP. MDL. DP135</b> , 30,000 lb cap. @ 24" load center, Cat diesel, auto. trans, 180" lowered height, 197" lift height, side shift, cab, 92" forks, 1200 x 20 large pneumatic style cushion tires, 8,833 H.O.M., S/N 5DP00028 (Location H)
155	1	<b>JIG MILL, DEVLIEG MDL. 4H-60</b> , 40" x 60" T-slotted table, 4" spdl., 48" vert. headstock travel, spdl. spds: 26-1220 RPM, threads & feeds, rapid feeds, way covers, lube system, Accu-rite 3-axis D.R.O., UNDER POWER, S/N 8358 (Location J)
156	1	<b>TURBINE LASER ALIGNMENT SYSTEM, CASCADE ANALYTICS SERIES 60" MDL. EASY-LASER E960B</b> , new 2012 & unused, measuring probe w/60" max. stroke, color display w/graphs, software, laser transmitter & detector, Bluetooth wireless operation (unused) (Location J)
157	1	<b>GAP BED ENGINE LATHE, YAMAZAKI 24" x 160" MDL. MAZAK-24</b> , 20" dia. 4-jaw chuck, spds: 12-1200 RPM, eng/met thdng., taper, 4" spdl. hole, steadyrest, full length leadscrew, toolpost, S/N 30057 (Location K)
158	1	<b>GAP BED ENGINE LATHE, YAMAZAKI 20" x 144"</b> , 12" dia. 3-jaw chuck, spds: 25-1500 RPM, thdng., taper, 3" spindle hole, steadyrest, full length leadscrew, S/N 32156 (Location K)
159	1	<b>ENGINE LATHE, AXELSON 22.5" x 72"</b> , Size 18 inch, speeds: 9.5 - 961, 10 HP motor, full length leadscrew, 2-5/8" spindle hole, thdng, taper, steadyrest, S/N N.A. (Location K)
160	1	<b>TELEPHONE SYSTEM, AT&amp;T PARTNER II</b> , Avaya & Lucent handsets, 8-line capability (Location L)
161	1	<b>LOT OF CREDENZAS, DESK, END TABLES &amp; CHAIRS</b> (Location L)
162	1	<b>FORKLIFT, TAYLOR 52,000 LB. CAP. MDL. TC-520</b> , 114" std. mast, diesel, cushion tires, 60" forks, fork positioner, 5,400 H.O.M., S/N S-D1-19942 (Location M)
163	1	<b>FORKLIFT, CLARK 12,000 LB. CAP. MDL. CGP55</b> , new 2001, 92" dia. 3-stage mast, 178" lift. ht., side shift, LPG, dual drive pneu. tires, 48" forks, S/N CGP460L -0218-GEF-9612 (Location M)

<u>LOT</u>	<u>QTY</u>	<u>DESCRIPTION</u>
164	1	<b>FORKLIFT, CLARK 10,000 LB. CAP. MDL. GCX50</b> , new 1997, 87" dia. 3-stage mast, 188" lift ht., cushion tires, side shift, LPG, 42" forks, 4222.5 H.O.M., S/N GX710U-0051-9457FB (Location M)
165	1	<b>FORKLIFT, YALE 8,000 LB. CAP. MDL. GDP080</b> , new 2004, 98" dia. 3-stage mast, 206" lift. ht., side shift, diesel, pneu. tires, 48" forks, S/N E813V01534B (Location M)
166	1	<b>FORKLIFT, YALE 5,000 LB. CAP. MDL. GLC050</b> , new 2001, 84" dia. 3-stage mast, 194" lift ht., side shift, LPG, cushion tires, 42" forks, S/N 187V17229Y (Location M)
167	1	<b>FORKLIFT, YALE 5,000 LB. CAP. MDL. GLC050</b> , new 2000, 82" dia. 3-stage mast, 189" lift ht., side shift, LPG, cushion tires, 42" forks, S/N E187V13854X (Location M)
168	1	<b>OVERHEAD BRIDGE CRANE, ROBBINS &amp; MYERS 5 T. X 37' SPAN</b> , Mdl. SIB-OH-MD, top riding bridge, underslung hoist, dual I-beam design, Shaw-Box 5 T. cap. Mdl. LiftTech wire cable hoist, pendant control, S/N C-2094 (Location N)
169	1	<b>OVERHEAD BRIDGE CRANE, ROBBINS &amp; MYERS 3 T. X 29' SPAN</b> , top riding bridge, underslung hoist, Robbins & Myers 3 T. wire cable hoist, Mdl. 5C-5-26 w/Shaw-Box pendant control, S/N N.A. (Location N)
170	1	<b>FREE-STANDING OVERHEAD BRIDGE CRANE SYSTEM, GAFFEY 10 T. CAP. TOP RUNNING DOUBLE GIRDER DESIGN</b> , new 1995, approx. 70' span, approx. 160' dual runway, 30' ht. structural steel uprights, S/N 51012BH01 (Note: Currently disassembled and ready for loading) (Location P)
171	1	<b>MAGNETIC LIFTING DEVICE, O.S. WALKER MDL. CM-800 Toter</b> , 1,760 lbs. smooth surface rating for 1.5" thk. steel (Location K)
172	1	<b>MAGNETIC LIFTING DEVICE, O.S. WALKER MDL. CM-800 Toter</b> , 1,760 lbs. smooth surface rating for 1.5" thk. steel (Location K)
173	1	<b>ELECTRIC CHAIN HOIST, COFFING 1 T. CAP.</b> , pendant control (Location K)
174	1	<b>ELECTRIC CHAIN HOIST, BUDGIT ½ T. CAP.</b> , pendant control (Location K)
175	1	<b>ELECTRIC CHAIN HOIST, BUDGIT ½ T. CAP.</b> , chain pull control (Location K)
176	1	<b>ELECTRIC CHAIN HOIST, LOADSTAR SERIES 627</b> , pendant, trolley (Location K)
177	1	<b>ELECTRIC CHAIN HOIST, HITACHI ½ T. CAP.</b> , pendant, trolley (Location K)
178	1	<b>ELECTRIC CHAIN HOIST, BUDGIT ½ T. CAP.</b> (Location K)
179	1	<b>MANUAL CHAIN HOIST, YALE 1-1/2 T. CAP.</b> (Location K)
180	1	<b>MANUAL CHAIN HOIST, YALE EATON 1 T. CAP.</b> (Location K)
181	1	<b>CHAIN HOIST, JET 1 T. CAP.</b> , trolley, no chain, for repair (Location K)
182	1	<b>ELECTRIC CHAIN HOIST, JET 1 T. CAP.</b> , for repair (Location K)
183	1	<b>ELECTRIC CHAIN HOIST, BUDGIT</b> , for repair (Location K)
184	1	<b>ELECTRIC CHAIN HOIST, BUDGIT</b> , for repair (Location K)
185	1	<b>ELECTRIC CHAIN HOIST, CM ½ T. CAP.</b> , no pendant, for repair (Location K)
186	1	<b>ELECTRIC CHAIN HOIST, DEMAG 1/4 T. CAP.</b> , pendant ctrl., for repair (Location K)